



MAIN FEATURE

1. Slim type with 16A rated load.
2. 8 mm insulation distance.
3. Dielectric strength 5,000V and surge strength up to 10,000V.
4. UL Class F insulation available.
5. High sensitivity DC coil type of low power consumption available.
6. Halogen Free series available.
7. Comply with RoHS and REACH regulations.

CONTACT RATING

Load Type	MIH (DM/LM/DB/LB)	MIH (D/L)
Rated Load (Resistive)	16A 240VAC	16A 240VAC
	16A 24VDC	16A 24VDC
	1/3 HP 120VAC	1/3 HP 120VAC
	-	-
Rated Carrying Current	16A	16A
Max. Allowable Voltage	AC: 250V	AC: 250V
	DC: 110V	DC: 110V
Max. Allowable Current	16A	16A
Max. Allowable Power Force	3840VA	3840VA
	384W	384W
Contact Material	Ag Alloy	Ag Alloy
Contact Form	SPST	SPDT

APPLICATION

Cooking Appliances, Air Conditioner, Audio Equipment, Domestic Appliances, Controlling Equivalent, etc.

PERFORMANCE (AT INITIAL VALUE)

- Contact Resistance 100mΩ Max. @1A, 6VDC
- Operate Time 15mSec. Max. (D Type)
20mSec. Max. (L Type)
- Release Time 8 mSec. Max.
- Dielectric Strength:
 - Between Coil & Contact 5,000VAC at 50/60 Hz for one minute
 - Between Contacts 1,000VAC at 50/60 Hz for one minute
- Surge Strength 10,000V (between Coil & Contact 1.2x50μSec.)
- Insulation Resistance 100 MegaΩ Min. at 500VDC
- Max. On/Off Switching:
 - Electrical 6 Cycles per Minute
 - Mechanical 300 Cycles per Minute
- Temperature Range -30~+70°C
- Humidity Range 45~85% RH.
- Coil Temperature Rise 45°C Max. (D Type)
35°C Max. (L Type)
- Vibration:
 - Destruction 10 to 55 to 10 Hz, 0.75 mm single amplitude (1.5mm double amplitude)
 - Malfunction 10 to 55 to 10 Hz, 0.75 mm single amplitude (1.5mm double amplitude)
- Shock:
 - Destruction 1,000 m/S²
 - Malfunction 100 m/S²
- Life Expectancy:
 - Mechanical 10⁷ Operations at No Load condition
 - Electrical 10⁵ Operations at Rated Resistive Load
- Weight About 12.2 g

SAFETY STANDARD & FILE NUMBER

- UL & CUL E141060
- TÜV (MI) R09552084
- TÜV (MIH) R09854160
- VDE (MI-L/LM/D/DM Type) . 40013086

COIL SPECIFICATION (AT 20°C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ($\Omega \pm 10\%$)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
MIH D/DM/DB	3	240	12.5	Abt. 0.72	80% Maximum	5% Minimum	130%
	5	138.9	36				
	6	120	50				
	9	78.3	115				
	12	60	200				
	24	29.3	820				
	48	14.5	3,300				
MIH L/LM/LB	3	176.5	17	Abt. 0.54	80% Maximum	5% Minimum	130%
	5	106.4	47				
	6	88	68				
	9	58	155				
	12	44.4	270				
	24	21.8	1,100				
	48	10.9	4,400				

ORDERING INFORMATION

MIH - SS - 1 12 D M F

Insulation System:

Nil: Standard Class

F: Class F

Contact Form:

Nil: One Form C

M: One Form A

B: One Form B (VDE only)

Coil Type:

D: Standard DC

L: High DC

Coil Voltage: 03: 3V, 05: 5V, 06: 6V, 09: 9V, 12: 12V, 24: 24V, 48: 48V

Number of Pole: 1: One Pole

Type of Sealing:

SS: RT II Flux Proofed

SH: RT III Wash Tight

Type:

MIH

CLASSIFICATION





Model	MIH					
	Standard DC			High DC		
Coil Sensitivity						
Contact Form	1C	1A	1B	1C	1A	1B
Flux Proofed	MI(H)-SS-1□□D	MI(H)-SS-1□□DM	MI(H)-SS-1□□DB	MI(H)-SS-1□□L	MI(H)-SS-1□□LM	MI(H)-SS-1□□LB
Wash Tight	MI(H)-SH-1□□D	MI(H)-SH-1□□DM	MI(H)-SH-1□□DB	MI(H)-SH-1□□L	MI(H)-SH-1□□LM	MI(H)-SH-1□□LB

ACCESSORIES & SOCKETS

MI-1P

- PI-35BE See Page 140
- PI-35BE/3 See Page 140
- PI-35-0 See Page 141

Dimension ($\leq 5\text{mm} \pm 0.2\text{mm}$, $> 5\text{mm} \pm 0.3\text{mm}$, the tolerance of PCB thru hole: $+0.1\text{mm}$)



Bottom View

P.C.B Layout
Bottom View